

CATALYTIC HEATER SPECIFICATIONS

Heater Size (in)	Voltages (V)	Respective Starting Amperage (A)	BTU Rating (BTU/hr)	Approximate Weight (lbs.)	Hourly Fuel Consumption Natural Gas (SCFH)	Hourly Fuel Consumption Propane (lb/hr)
8 Round	12, 24, 120	6.7, 4.2, 0.6	2500	4	2.5	0.12
12 Round	12, 24, 120, 240	8.3, 4.2, 0.8, 0.4	5000	5	5.0	0.23
6x6	12, 24, 120	6.7, 4.2, 0.6	1500	5	1.5	0.07
8x8	12, 24, 120, 240	6.7, 4.2, 0.6, 0.4	2667	5	2.7	0.12
6x12	12, 24, 120, 240	8.3, 4.2, 0.8, 0.4	3000	7	3.0	0.14
10x12	12, 24, 120, 240	8.3, 4.2, 0.8, 0.4	5000	8	5.0	0.23
12x12	12, 24, 120, 240	8.3, 4.2, 0.8, 0.4	6000	10	6.0	0.28
6x24	12, 24, 120, 240	16.7, 4.2, 1.9, 1.9	6000	10	6.0	0.28
12x24	12, 24, 120, 240, 480	16.7, 8.3, 1.7, 0.8, 0.4	12000	15	12.0	0.56
12x36	12, 24, 120, 240, 480	33.3, 16.7, 3.8, 1.9, 1.9	18000	20	18.0	0.83
12x48	12, 24, 120, 240, 480	33.3, 16.7, 3.8, 1.9, 1.9	24000	30	24.0	1.11
24x24	12, 24, 120, 240, 480	33.3, 16.7, 3.8, 1.9, 1.9	24000	30	24.0	1.11
18x36	12, 24, 120, 240, 480	33.3, 16.7, 3.8, 1.9, 1.9	27000	30	27.0	1.25
12x60	12, 24, 120, 240, 480	33.3, 16.7, 3.8, 1.9, 1.9	30000	40	30.0	1.39
18x48	12, 24, 120, 240, 480	33.3, 16.7, 3.8, 1.9, 1.9	36000	40	36.0	1.67
18x60	12, 24, 120, 240, 480	33.3, 16.7, 3.8, 1.9, 1.9	45000	45	45.0	2.08
24x48	12, 24, 120, 240, 480	33.3, 16.7, 8.3, 4.2, 2.1	48000	45	48.0	2.22
24x60	12, 24, 120, 240, 480	33.3, 16.7, 8.3, 4.2, 2.1	60000	60	60.0	2.78
24x72	12, 24, 120, 240, 480	33.3, 16.7, 8.3, 4.2, 2.1	72000	65	72.0	3.33