



Item	Description
A	Inlet Pressure / 1500 psig max.
B	High Supply Pressure / 100 – 135 psig
C	Low Supply Pressure / 20 – 40 psig

Item	Description
1	Filter Inlet Valve / ¼ in Full Port 316 SS Ball Valve / 2000 psig MAOP
2	Filter Bypass Valve / ¼ in Full Port 316 SS Ball Valve / 2000 psig MAOP
3	Filter Outlet Valve / ¼ in Full Port 316 SS Ball Valve / 2000 psig MAOP
4	Filter Dryer / IMAC Model FD5 Std. / 100% Silica Gel / 1500 psig MAOP
5	High Supply Regulator / FISHER Brand 1301 / Brass / Tapped Exhaust
6	High Supply Gage / 2.5 in DIA / 316 SS Liquid Filled
7	High Supply Relief / Brass / ½ NPT / Non Adjust. / 150 psig

Item	Description
8	Low Supply Regulator / FISHER Brand 67FR / AL / Tapped Exhaust
9	Low Supply Gage / 2.5 in DIA / 316 SS Liquid Filled
10	Low Supply Relief / Brass / ½ NPT / Non Adjust. / 50 psig
11	Drain Valve / ¼ in Needle Valve 316 SS
--	Mounting Bracket / Painted Steel – NOT SHOWN