



Item	Description
<b>A</b>	Inlet Pressure / 1500 psig max.
<b>B</b>	High Supply Pressure / 100 – 135 psig
<b>C</b>	Low Supply Pressure / 20 – 40 psig

Item	Description
1	Filter Inlet Valve / ¼ in Full Port 316 SS Ball Valve / 2000 psig MAOP
2	Filter Dryer / IMAC Model FD5 Std. / 100% Silica Gel / 1500 psig MAOP
3	Drain Valve / ¼ in Needle Valve 316 SS
4	High Supply Regulator / Fisher Type 1301 / Stainless Steel / Tapped Exhaust
5	High Supply Gage / 2.5 in DIA / 316 SS Liquid Filled
6	Downstream Outlet Valve / ¼ in Full Port 316 SS Ball Valve / 2000 psig MAOP
7	High Supply Relief REGO / Stainless Steel / ½ NPT / Non Adjust. / 150 psig

Item	Description
8	Low Supply Regulator / Fisher Type 67/ Stainless Steel / Tapped Exhaust
9	Low Supply Gage / 2.5 in DIA / 316 SS Liquid Filled
10	Low Supply Relief REGO / Stainless Steel / ½ NPT / Non Adjust. / 50 psig
--	Mounting Bracket / Painted Steel – NOT SHOWN