



ENDURO
PIPELINE SERVICES, INC.

P.O. Box 3489 | Tulsa OK 74101-3489
Toll free 800-752-1628 | Office 918-446-1934
<https://www.enduropls.com>

APPEARANCE	STYLE	TYPE	DENSITY	APPLICATIONS
	G1	Swab	<u>1-2 lbs. cubic foot</u> (16 - 32 Kg/M3)	Light Duty Drying
	G2*	Coated Swab	<u>1-2 lbs. cubic foot</u> (16 - 32 Kg/M3)	Light Duty Wiping
	G6*	Carbide (Grain)	<u>1-2 lbs. cubic foot</u> (16 - 32 Kg/M3)	Light Duty Scraping
	RX3	Bare	<u>5-7 lbs. cubic foot</u> (80 - 112 Kg/M3)	Regular Duty Drying
	RX4*	Coated	<u>5-7 lbs. cubic foot</u> (80 - 112 Kg/M3)	Regular Duty Wiping
	RX5*	Wire	<u>5-7 lbs. cubic foot</u> (80 - 112 Kg/M3)	Regular Duty Scraping
	RX6*	Carbide (Grain)	<u>5-7 lbs. cubic foot</u> (80 - 112 Kg/M3)	Regular Duty Scraping
	C3	Bare	<u>8-10 lbs. cubic foot</u> (128 - 160 Kg/M3)	Heavy Duty Drying
	C4*	Coated	<u>8-10 lbs. cubic foot</u> (128 - 160 Kg/M3)	Heavy Duty Wiping
	C5*	Wire	<u>8-10 lbs. cubic foot</u> (128 - 160 Kg/M3)	Heavy Duty Scraping
	C6*	Carbide (Strap)	<u>8-10 lbs. cubic foot</u> (128 - 160 Kg/M3)	Heavy Duty Scraping

*Available in rotating pattern